

# Compact and smart

imageRUNNER ADVANCE  
500i, 400i

you can

Suitable for busy workgroups and departments, these compact imageRUNNER ADVANCE devices offer efficient mono output and intelligent document handling to optimise your workflows, save you money and secure your confidential information.

40-50 PPM MONO

imageRUNNER ADVANCE PLATFORM

SPACE SAVING, MODULAR DESIGN

17.8 CM COLOUR TILTABLE TOUCH SCREEN

UP TO 2300 SHEET CAPACITY

UP TO A4 OUTPUT

AUTOMATIC STAPLE FINISHING OPTION



## Productivity

- Unrivalled and consistent user experience through a large 17.8cm tiltable colour touch screen and intuitive menus
- Unique personalisation capabilities simplify and automate commonly performed tasks by user
- Colour duplex scanning and sending with native support for data formats such as searchable PDF and Open Office XML (Powerpoint) enables re-use and re-purpose of digital content
- Integration with powerful document, capture and output management solutions provide process optimisation
- Up to 2,300 sheet paper capacity for busy workgroups and departments
- Time-saving automatic staple finishing option
- Support for mobile working.

## Cost Control

- The functionality of many devices in one compact multifunctional device
- Efficient and reliable monochrome output for workgroups and departments
- User-based activity tracking provides visibility of print behaviour
- Apply policies and restrict usage at function level by user
- Efficient device monitoring, reporting and diagnostics for easy management and maintenance
- Ability to use shared resources, such as fax and Advance Space, from other iR-ADV devices
- Options for cost recovery and coin vending integration.

 **imageRUNNER**  
ADVANCE

**Canon**

### Device and Information Security

- Award-winning and smart user authentication ensures control without impacting on user productivity or convenience
- Ability to disable functions by user to prevent unauthorised usage
- Secure Print and MailboxLite enhance document confidentiality
- A variety of standard features such as data erase, IP and MAC address filtering and IPSec protects the device and network data transfer
- An extensive range of options offer compliance to highest levels covering all aspects of information security
- Industry-first Data Loss Prevention and auditing of prints, copies, scans and faxes through uniFLOW.


### Integration

- Versatile imageRUNNER ADVANCE portfolio addresses the needs of all workplaces from small workgroups through to large departments and Corporate Reprographic Departments
- Native support for industry and network standards i.e. Genuine Adobe PostScript and PCL ensures hassle-free integration with ERP, CRM and other business information systems
- Consistent imageRUNNER ADVANCE platform and portfolio simplifies management and operation across a fleet
- Canon's powerful embedded MEAP & MEAP Web platform provides a strong link to a range of award-winning document, capture and output management solutions for process optimisation
- Easily configure, manage and upgrade your device, whether individually, or as part of a larger fleet using Canon's device management tools
- Shared resources across the network.

### Sustainability

- Class leading Typical Electricity Consumption (TEC)\* ratings
- Consumes as little as 1 W in sleep mode
- Incorporates recycled materials and bio-plastics
- ENERGY STAR® qualified.

### Main configuration options



For full details of all options, please refer to the product specifications.

\*Defined by ENERGY STAR (<http://www.eu-energystar.org>)

# Specifications: imageRUNNER ADVANCE 500i/400i series

Machine type	Monochrome A4 Laser Multifunctional (Reader/Printer standard)
Available Core functions	Print, Copy, Scan, Send and optional Fax
<b>PRINTER SPECIFICATIONS</b>	
Print speed (BW)	iR-ADV 500i: Up to 50 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 49ppm (A4 Double-sided), 22ppm (A5 Double-sided) iR-ADV 400i: Up to 40 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 39ppm (A4 Double-sided), 22ppm (A5 Double-sided)
Printing method	Monochrome Laser Beam Printing
Print resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Double sided printing	Automatic (Standard)
Printing from memory media	Direct printing available from USB memory key, Remote UI and Web Access* Supported file types: JPEG, TIFF, PDF, XPS** (* XPS print from websites is not supported) (** XPS requires DIRECT PRINT KIT (for PDF/XPS)-H1)
Printing from mobiles or internet-connected devices and cloud-based services	A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Paper input (Standard)	1 x 550-sheet(80 gsm) cassette, 100-sheet(80 gsm) multi-purpose tray
Paper input (Option)	Up to 3 x 550-sheet cassettes (80 gsm) (Cassette Module-AA1)
Maximum paper input capacity	2300 sheets (80 gsm)
Paper output capacity	Without Finisher: 250 sheets (80 gsm) With Staple Finisher: 500 sheets without stapling (80gsm), 20 sets with stapling
Finishing capabilities	Standard: Group Optional Staple Finisher: Collate, Group, Staple Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Bond, Transparency, Label, Letterhead, Bond paper, Envelope.
Supported media types	<b>Cassette/s:</b> Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelope* *Envelope support via drawer 2 only. Requires optional Envelope Cassette-E1 Multi-purpose tray. <b>Paper Drawer 2:</b> Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Bond, Transparency, Label, Envelope (No.10 (COM10), Monarch, ISO-CS, DL)
Supported media sizes	<b>Paper Drawer 1, 3 and 4:</b> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement <b>Paper Drawer 2:</b> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes* (No.10 (COM10), Monarch, ISO-CS, DL) *Requires optional Envelope Cassette-E1 Multi-purpose tray. Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (99 mm to 216 mm x 140 mm to 356 mm), Envelopes (No.10 (COM10), Monarch, ISO-CS, DL)
Supported media weights	<b>Cassette/s:</b> 64 to 105 g/m <sup>2</sup> Multi-purpose tray: 64 to 128 g/m <sup>2</sup> Duplex: 64 to 105 g/m <sup>2</sup>
Page Description Language(s)	UFRII, PCL5e/6, Adobe PostScript Level 3 (Standard on all models)
Fonts	PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts, Andale 4 PS fonts: 136 Roman fonts
Operating System compatibility	UFRII: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008R2/Windows 8/Server 2012, MAC OS X (10.5.8 or later) PCL: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012 PS: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012, MAC OS X (10.5.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows 2000/Windows XP/Windows Vista/Windows 7/Windows 8 Please refer to <a href="http://software.canon-europe.com/">http://software.canon-europe.com/</a> for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place.
<b>COPY SPECIFICATIONS</b>	
Copy speed	iR-ADV 500i: Up to 50 ppm (A4) iR-ADV 400i: Up to 40 ppm (A4)
First Copy Output Time (FCOT)	Approx. 5.0 seconds or less
Copy resolution	Reading: 600 dpi x 600 dpi Printing: 1200 dpi x 1200 dpi for characters/lines, 600 dpi x 600 dpi for graphics/images
Multiple copy	Up to 999 copies
Reduction/Enlargement	Zoom: 25-400 % in 1 % increments Fixed Zoom Ratio: 25 %, 50 %, 70 %, 100 %, 141 %, 200 %, 400 %
<b>SCAN SPECIFICATIONS</b>	
Optional/Standard	Standard on all models
Supported media size/s	A4, A5, B5, Custom sizes (W x L): Min. 140 mm x 140 mm, Max. 356 mm x 216 mm
Supported media weight/s	Single-sided scanning: 42 to 128 gsm/64 to 128 gsm (Mono/Colour), Double-sided scanning: 50 to 128 gsm/64 to 128 gsm (Mono/Colour)
Scan resolution	<b>Mono Scan:</b> 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi <b>Colour Scan:</b> 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi
Double sided scanning	2-sided to 2-sided (Automatic)
Scan speed (A4, 300 dpi)	Mono single-sided: 50 ipm/A4(600dpi/300dpi) Mono double-sided: 32 ipm/A4(600dpi/300dpi) Colour single-sided: 50 ipm/A4(300dpi) Colour double-sided: 32 ipm/A4(300dpi)
Scan methods	<b>Push Scan:</b> Colour Universal Send functionality is standard. Integration with a range of optional MEAP-based capture software adds powerful workflow and conversion capabilities. Please contact your sales representative for further information. <b>Pull Scan:</b> TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key Scan to Mobiles, internet-connected devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices, internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Pull scan specifications	TWAIN via Network TWAIN Driver (Colour Network ScanGear) Supported OS: Windows 2000/Windows XP/Windows Server 2003/Windows Vista/Windows Server 2008/Windows 7/Windows 8 (32 bit, 64 bit in compatibility mode)* WIA via Network WIA Driver Supported OS: Windows Vista/Windows Server 2008/Windows 7/Windows 8 (32 bit, 64 bit)* *The drivers are available via <a href="http://software.canon-europe.com/">http://software.canon-europe.com/</a> .
<b>SEND SPECIFICATIONS</b>	
Optional/Standard	Standard on all models
Send resolution	100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi
Destinations	E-Mail/Internet FAX (SMTP), Fax(option), PC (SMB, FTP, WebDAV), Google Drive with Cloud Connect for iR-ADV MEAP application
Address Book/Speed dials	LDAP(Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials)
File formats	TIFF, JPEG, PDF, XPS, PDF/XPS (compact), PDF/A-1b, Searchable PDF/XPS, Office Open XML (PowerPoint)
Optional Universal Send Feature Sets	UNIVERSAL SEND ADVANCED FEATURE SET-E1: Create outline PDF (Trace and Smooth) and Adobe Reader Extensions PDF. UNIVERSAL SEND SECURITY FEATURE SET-D1: Send encrypted PDF and add digital device signature to PDF/XPS files. UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1: Add digital user signature to PDF/XPS files.
<b>FAX SPECIFICATIONS</b>	
Optional/Standard	Optional on all models (requires SUPER G3 FAX BOARD-AM1)
Modem speed	Super G3 33.6kbps (Up to 3 seconds per page (see footnote 1))
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
FAX memory	Up to 6000 pages (see footnote 1)
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes (Approx. 3 hours)
Other features	Fax Forwarding, Dual Access, PC Fax (TX only)
<b>GENERAL SPECIFICATIONS</b>	
Warm-up Time	Approx. 34 seconds from power ON (Normal mode), 10 seconds from power ON (Quick Start mode)
Recovery from sleep mode	10 seconds or less
Interface type	USB 2.0 Hi-Speed, 1000BaseT/100Base-TX/10Base-T, 1 x USB Host (Front), 2 x USB Host (Rear)
Network protocols	TCP/IP* (LPD/Port 9100/WSD/IPP/PPS/SMB/FTP), IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support. Recommended third party wireless solution is Silex SX-2500CG. For more details please refer to <a href="http://www.silex-europe.com">www.silex-europe.com</a>
Processor/Speed	1.66 Ghz
Memory	1.5 GB
Hard Disk Drive	160 GB Hard Disk Drive (Usable space 80 GB)
Control panel	17.8 cm (7 inch) WVGA Colour TFT LCD Touch & Tilttable Panel
Dimensions (W x D x H)	560 mm x 567 mm x 633 mm (standard) 560 mm x 567 mm x 752 mm (with 1 optional cassette) 560 mm x 567 mm x 868 mm (with 2 optional cassettes) 560 mm x 567 mm x 984 mm (with 3 optional cassettes)
Installation space (W x D)	787 mm x 567 mm (Main unit + Multi-purpose tray open + Cassette drawers closed) 1182 mm x 567 mm (Main unit + Staple Finisher + Multi-purpose tray open + Cassette drawers closed)
Weight	47.9kg excluding Toner
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80 % RH (no condensation)
Power Source	220-240 V (±10 %), 50/60 Hz (±2 Hz), 4-5.3-6 Amp
Power Consumption	Maximum: Approx. 1.6 KW Standby: Approx. 53.72 W Sleep mode: Approx. 1 W or less (see footnote 2) Typical Electricity Consumption (TEC) rating (see footnote 3): 2.4 kWh (iR-ADV 500i) / 1.873 kWh (iR-ADV 400i)
Noise Levels	Sound Pressure (see footnote 4) Active: 75 dB or less (iR-ADV 500i), 73 dB or less (iR-ADV 400i) Standby: 53 dB or less
Software and printer management	<b>MEAP (Multifunctional Embedded Application Platform):</b> A powerful JAVA Embedded Platform for Canon devices which integrates the device with a wide range of Canon and third party software solutions. <b>Universal Login Manager:</b> iR-ADV software for smaller businesses offering convenient login, personalisation as well as user-based usage tracking and control by function. <b>mobile PRINT &amp; SCAN:</b> Simple serverless iR-ADV software enabling printing from and scanning to Android and iOS mobiles and tablets. <b>MEAP Web:</b> Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services <b>iW Management Console:</b> Server-based software for centralised management of a fleet of devices <b>eMaintenance:</b> embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. <b>Content Delivery System:</b> Allows the remote distribution of firmware, iR options and MEAP applications. <b>Remote User Interface (RUI):</b> Web-based interface to each device that helps to provide remote device management and control. <b>Colour Network ScanGear:</b> TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device. <b>Canon Driver Configuration Tool:</b> A utility for changing the factory default settings of Canon print drivers (Available via service only) <b>iW DESKTOP:</b> Drag-and-Drop print publishing software to easily combine documents and apply finishing to create professional-looking documents <b>REMOTE OPERATORS SOFTWARE:</b> Allows use of device control panel screens from remote computers. For details of other software including MEAP software, please contact your sales representative
Security Features	Standard: IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, HDD Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, Access Management System. Optional: Encrypted Secure Print, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite. The following items require uniFLOW: My Print Anywhere secure print, Data Loss Prevention.

# Specifications: imageRUNNER ADVANCE 500i/400i series

CONSUMABLES	
Toner bottle	C-EXV 43 Black Toner (Yield: 15200 pages (see footnote 5))
OTHER OPTIONS	
Staple Finisher 1	<b>STAPLE FINISHER-R1</b> Number of Trays: 1 Stack Capacity: With stapling: 20 sets. Without stapling: 500 sheets Maximum Stapling capacity: Up to 50 sheets Paper Weight: 64 to 120 g/m <sup>2</sup> Staple Position: Single (Top-Left) Dimensions (W x D x H): 798 mm x 395 mm x 263 mm Weight: Approx. 10.5 kg
Staple Finisher 2	N/A
Booklet Finisher	N/A
Cassette module	<b>CASSETTE MODULE-AA1</b> Description: Optional cassette module with 550 sheets paper capacity. Up to 3 cassette units can be added to a main unit Dimensions (W x D x H): 540 mm x 500 mm x 119 mm Weight: Approx. 7.7 kg
Hardware accessories 1	<b>PLAIN PEDESTAL TYPE-B1:</b> The pedestal can be placed under the standard/optional cassette module to raise the device when free-standing. This is a higher pedestal suitable for use with the standard cassette or one additional cassette module. (Height of Pedestal: 300 mm) <b>PLAIN PEDESTAL TYPE-C1:</b> The pedestal can be placed under the standard/optional cassette module to raise the device when free-standing. This is a lower pedestal suitable for use with an additional two or three cassette modules. (Height of Pedestal: 94 mm) <b>ENVELOPE CASSETTE-E1:</b> Attaches to cassette "2" for easy envelope feeding.
Hardware accessories 2	<b>MICARD PLUS PROXIMITY CARD READER:</b> A proximity card reader for card-based user authentication, supporting multiple card technologies (HID, HiTag, Casi Rusco, Indala and MiFare etc.).
Print controller accessories	<b>BARCODE PRINTING KIT-D1:</b> Enables barcode printing via jet caps technology.
Document publishing	<b>iW DESKTOP:</b> Drag-and-Drop print publishing software which easily combines documents from different sources, applies finishing to create professional looking documents and seamlessly links to the printer. Includes PDF creation, annotation and compression capabilities for digital workflows such as proofing and authorization.

System accessories	<b>WEB ACCESS SOFTWARE-J1:</b> Provide access to websites and MEAP Web applications. <b>SUPER G3 FAX BOARD-AM1:</b> Adds fax functionality. <b>SUPER G3 2ND LINE FAX BOARD-AM1:</b> Adds second fax line. <b>REMOTE FAX KIT-A1:</b> Enables the device to send and receive fax from another compatible device connected with a fax board. <b>IC CARD READER BOX-A1:</b> A Box to hold and secure an IC Card Reader such as MiCard Reader to the device. <b>COPY CONTROL INTERFACE KIT-A1:</b> Allows connection (CCV I/F) between 3rd party copy control terminal and Canon's iR-ADV range for cost recovery use.
Device security accessories	<b>HDD DATA ENCRYPTION KIT-C6:</b> Encrypts all image data and device settings before storing them on the hard drive of the device.
Document security accessories	<b>SECURE WATERMARK-B1:</b> Deters duplication of sensitive documents by embedding hidden watermarks that become visible when copied. <b>ENCRYPTED PRINTING SOFTWARE-D1:</b> Encrypts the printjob in transit to the device and requires a password at the printer before sensitive documents can be printed.
Accessibility accessories	<b>ADF ACCESS HANDLE-A1:</b> Attaches to the document feeder, making access easier for seated users. <b>REMOTE OPERATORS SOFTWARE KIT-B1:</b> Allows use of device control panel screen from remote computers.
Other options	<b>STAPLE-P1:</b> Plain staples for Staple Finisher-R1
STANDARD DISCLAIMERS	
All specifications subject to change without notice	
Footnotes	
[1]	Based on ITU-T Standard Chart No.1
[2]	1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information.
[3]	Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star ( <a href="http://www.eu-energystar.org">http://www.eu-energystar.org</a> ).
[4]	Declared noise emission in accordance with ISO 7779
[5]	Based on 6% coverage (A4)

## Awards



## Software and Solutions



## Certifications and compatibility



All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.  
canon.com  
  
Canon Europe  
canon-europe.com  
  
English  
© Canon Europa N.V., 2013

Canon (UK) Ltd  
  
Woodhatch  
Reigate  
Surrey RH2 8BF  
Telephone no 01737 220000  
Facsimile 01737 220022  
canon.co.uk

Canon Ireland  
  
3006 Lake Drive  
Citywest, Saggart  
Co.Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

